

EXP40

Expansion Module for the SIP-T46GN and SIP-T48GN

Expanding the functional capability of the above phones

Large graphic LCD

Two pages of 20 flexible buttons

Program up to 40 various features

Adjustable stand with two angles

Wall mountable



High-Performance LCD Expansion Module

The EXP40 is designed to match the stylish look and feel of T46GN and T48GN with rubber feet and new foot stand allowing two positions for the device, as well as wall mountability. The backlit display eliminates the need for external light. The unit is easy to install, simply link EXP40 to the EXT port of the phone

Equipped with a 160x320 graphic LCD with Backlight, 20 physical keys each with a dual-color LED and two page views are possible. This allows 40 additional programmable keys that can be used for speed dialing, BLF/BLA, call forward, transfer, park, pickup, etc. Two independent control keys are used for fast switch between pages.

As an attendant console application up to 6 expansion modules can be supported adding up to 240 additional buttons. More than two connections must be powered by a conventional power supply (5V/1.2A).

EXP40

Display

160x320 graphic LCD with 16-level
grayscale
LCD Backlight
Two page views are possible
Different icons for each function shown
on the LCD

Feature keys and indicators

20 physical keys each with a dual-colour
LED
20 additional keys through page switch
2 independent control keys are used for
fast switch between pages
Programmable for shared line, BLF List,
call park, conference, forward, group
pickup,
group listening, LDAP, Pick UP, XML
Browser

Physical Features

Wall mountable
Stand with 2 adjustable angles
Expansion module (≤ 2) is powered by
the host phone
Supports up to 6 modules daisy-chain
2xRJ12 (6P6C) ports for data in and out
Dimension (W*D*H*T):
127mm*213mm*167mm*45mm
Applies to Yealink IP Phone
Operating temperature: -10~50°C
Operating humidity: 10-95%

Packaging

Qty/CTN: 10 PCS
N.W/CTN: 6.7 kg
G.W/CTN: 7.6 kg
Giftbox size: 237mm*154mm*100mm
Carton Meas: 520mm*317mm*247mm

Certifications



WEEE Compliant



ROHS Compliant



T46GN with EXP40



Yealink
EASY VoIP